

# Revel F328Be

3-way Triple 8" Floorstanding Loudspeaker

REVEL®

PERFORMA **Be**<sup>4</sup>™



The Revel F328Be is the flagship floorstanding loudspeaker from our award-winning PerformaBe series. The F328Be includes a 1-inch (25mm) beryllium tweeter driven by massive 85mm dual ceramic magnets. The powerful all-new tweeter and 6th-generation ceramic-coated, cast-aluminum Acoustic Lens waveguide seamlessly integrate with the directivity of the companion midrange driver resulting in greater efficiency, improved dynamic range, reduced distortion, and increased power handling compared to aluminum or titanium tweeters.

Beryllium – Element 4 on the Periodic Table – is a rare earth metal that is renowned for its remarkable physical properties that make it the ideal material for a high-frequency transducer. Compared to aluminum and titanium tweeter diaphragms, Beryllium offers 4.5 times the stiffness and three times more damping, and does so at only half of the weight. Beryllium tweeters are the centerpiece of the Revel PerformaBe loudspeaker series.

The 5.25-inch (130mm) midrange and triple 8-inch (200mm) aluminum cone woofers utilize Deep Ceramic Composite (DCC) cones for improved performance. DCC is a plasma electrolytic oxidation process that uses a plasma discharge to create a coarse ceramic coating on both sides of the aluminum core. The deep ceramic layers sandwiching the aluminum core provide constrained layer damping that push cone breakup modes outside of the passband allowing the driver to maintain ideal piston motion throughout its range. DCC cones combine with optimized motor magnetics to deliver improved mid- and low-frequency performance.

# Revel F328Be

3-way Triple 8" Floorstanding Loudspeaker

REVEL®

PERFORMA Be<sup>4</sup>™



## Highlights:

- Flagship floorstander for the PerformaBe range
- 1-inch Beryllium Dome Tweeter
- 6th-generation Acoustic Lens Waveguide
- Deep Ceramic Composite (DCC) Cone Midrange and Woofers
- High-order Crossovers with Film Capacitors and Air Core Inductors
- Magnetically Attached Grilles
- 4 Premium high-gloss finishes available

## Specifications:

Type	3-way triple 8" floorstanding loudspeaker
Low-frequency transducer	Three 8" (200mm) Deep Ceramic Composite aluminum cones, with cast frames
Midrange transducer	5-1/4" (130mm) Deep Ceramic Composite aluminum cone, with cast frame
High-frequency transducer	1" (25mm) Beryllium dome, with acoustic lens waveguide
Recommended amplifier power range	50 – 300 watts
Frequency response	26Hz – 40kHz (–6dB)
Low-frequency extension	24Hz (–10dB); 26Hz (–6dB); 35Hz (–3dB)
Nominal impedance	8 ohms
Sensitivity (2.83V/1m)	91dB
Crossover frequencies	240Hz; 2.1kHz
Enclosure type	Bass-reflex via dual rear-mounted ports
Inputs	Dual gold-plated binding posts with shorting straps
Available high-gloss finishes	Black, White, Metallic Silver, and Walnut
Dimensions with grille and base (H x W x D)	50.9" x 13.5" x 17.6" (1294mm x 341.3mm x 448.5mm)
Product Weight	112.6 lb (51.0kg)